


WTTB CT KIT 3PH+E+VT

6 mm²

3-Phase make-before-break CT test disconnect/shorting link kit with PE connection and VT connections.



Width/Height/Depth	mm
Rated current / max. cond. cross-section	A/mm ²
Max. clamping range	mm ²

93.1 x 100 x 79
30 / 10
0.5...10

Technical Data

Rated Data	
Rated voltage	V
Rated current	A
Nom. wire cross-section	mm ²
Rated impulse withstand voltage / Pollution severity	
Gauge to IEC 60947-1 / UL 94 flammability rating	
Type of mounting	
Type of connection	
Disconnect technology	
Net Weight	
Clamped conductors	
Solid / Stranded	mm ²
Flexible with ferrule	mm ²
Stripping length / Blade size	mm/-
Note	

IEC 60947-7-1		
IEC	UL	CSA
500		
30		
6		
	6 kV / 3	
	A4 / V-0	
TS 32 / TS 35		
Screw		
Make-before-break		
400g		
Rated connection		
0.5...10 / 0.5...10		
0.5...6		
12 / 0.8 x 4.0 mm		

Ordering Data

Version
Note

Type	Qty.	Order no.
WTTB CT KIT 3PH+E+VT	1	7940127532

Circuit diagram

