

ATTB CT KIT 1PH

6 mm²

1-Phase make-before-break CT test disconnect/shorting link kit.



| | |
|--|-------------------|
| Width/Height/Depth | mm |
| Rated current / max. cond. cross-section | A/mm ² |
| Max. clamping range | mm ² |

18.2 x 100 x 79
30 / 6
0.5...6

Technical Data

| Rated Data | |
|--|-----------------|
| Rated voltage | V |
| Rated current | A |
| Nom. wire cross-section | mm ² |
| Rated impulse withstand voltage / Pollution severity | |
| Gauge to IEC 60947-1 / UL 94 flammability rating | |
| Type of mounting | |
| Type of connection | |
| Disconnect technology | |
| Net Weight | |
| Clamped conductors | |
| Solid / Stranded | mm ² |
| Flexible with ferrule | mm ² |
| Stripping length / Blade size | mm/- |
| Note | |

IEC 60947-7-1

| IEC | UL | CSA |
|-------------------|----------|-----|
| 500 | | |
| 30 | | |
| 6 | | |
| | 6 kV / 3 | |
| | A5 / V-0 | |
| TS 35 | | |
| PUSH IN | | |
| Make-before-break | | |
| 100g | | |
| Rated connection | | |
| 0.5...6 / 0.5...6 | | |
| 0.5...6 | | |
| 12 / 0.8 x 4.0 mm | | |
| Note | | |

Ordering Data

| Version |
|---------|
| |
| Note |

| Type | Qty. | Order no. |
|-----------------|------|------------|
| ATTB CT KIT 1PH | 1 | 7940127934 |
| Note | | |

Circuit diagram

