

OVERVIEW

The Smartlock Access Management Solution controls access to critical equipment housed in the access nodes of network infrastructure. The GSM Smartkey is one of the main building blocks of this Solution. It obtains and stores access rights to operate any of Smartlock's mechatronic locks and seals. The GSM Smartkey energises the locks with its rechargeable battery.

The GSM Smartkey manages all communication with the locks to authenticate the user and operate the system. Data communication to the software is provided by its internal GSM module. Access requests are preauthorised and downloaded to the internal memory of the GSM Smartkey, which has been uniquely assigned to a specific user.







TECHNICAL INFORMATION


MATERIALS	
Body	ABS plastic
ENVIRONMENTAL	
Operating Temperature	-10°C to 70°C, according to IEC 60068-2
Water Ingress Protection	Splash proof
POWER SOURCE	2Ah lithium ion battery
COMMUNICATION	
Upstream (to software)	Standard encrypted mobile network comms
Downstream (to lock)	Proprietary comms via probe antenna
MASS	125g
EXTERNAL DIMENSIONS	60mm x 26mm x 113mm (various antenna lengths available)
WARRANTY	24 months manufacturer's warranty
SOFTWARE	Smartlock Access Management System as a Service (SaaS)
INTERNAL MEMORY	Storage of 100x access rights
COMPATIBLE SYSTEMS	Monitoring of internal environment of access nodes (via IoT)
OPTIONS AND ACCESSORIES	 Various antenna lengths (30mm, 57mm, 150mm) Carry case kit, including charger



TECHNICAL DRAWING

Components







Technical

